



[Catalog Home](#)

Product Datasheet

ANDERSON FARGO

GD117 -- Copper Automatic Dead End



Copper Automatic Dead End, Copper, CW Conductor .36 - .37" (9.1 - 9.3 mm) , Flex Bail

Product Specifications

Category Image



Automatic Deadends

Copper and Aluminum
AAC, AAAC, ACAR, ACSR,
Copper & Copperweld®
Conductor

Series Image (Automatic)



GD-100 Series

Automatic Dead End

Flex Bail

Copper & Copperweld®
Conductor

PDF Catalog Page

[Click HERE to view the web page.](#)

Bail Option

Flex Bail

Type

Automatic

Material

Copper

Inhibitor Loaded

Yes

Shell Material

Copper Alloy

Bail Material

Stainless Steel

Diameter Range

.36 - .37 in (9.1 - 9.3 mm)

Conductor Range Minimum - Maximum

Cu 1/0 str (19), Cu 1/0 str (7), Cu 2/0 sol, CW 2A

Minimum Conductor Diameter

0.36

Maximum Conductor Diameter

0.37

Weight / Ea.

0.67 lbs

Standard Package

50

UPC Code

09635930816

Notes

Add "N" suffix for Neoprene coated bail.

Compressed Product Number

GD117

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.