



BURNDY Catalog Number
UPC Number
Description
Status

YA6CL2TC10
 7818100184466
 CU HYLUG- 6 STR- 10X5/8
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Straight
 1.94
 Standard
 Chamfered,Skived
 0.20
 Standard
 0.09
 0.54
 0.42
 0.62
 5/8

General

Number of Holes
 Product Description

2
 CU Compression Terminal Code
 Conductor, Beveled Entry, 2
 Hole/W/InspWindow,
 #6AWG(Code), 600V-35kV, #10
 Stud, 0.62 Spacing, STRD bbl, Tin -
 Electro Plated

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 N/A
 N/A
 6 AWG

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin - Electro Plated
 #10
 Blue
 Y
 7,374
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Y
 Y
 Compliant
 N
 N
 UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175