



BURNDY Catalog Number
UPC Number
Description
Status

K2A31U2N
 7818106001600
 TWO:6STR-350 NEMA
 Active

Web Use
 BURNDY Product Line

Dimensional

Width (in)	2.31
Length (in)	4.50
Bolt Hole Size (in)	0.50
Thickness	0.31
D - in	3.00
Pad Width (in)	2.31
E - in	1.75
N (in)	0.63

General

Number of Conductors	2
Number of Holes	2
Product Description	Aluminum Universal Terminal, 2 Conductor, 2 Hole, 6 AWG (Str)-350 kcmil, 1/2" Stud, 1.75" Stud Hole Spacing, 2 Screws, Al/Cu Rated, Tin Plated

Conductor(s)

Aluminum Size (Range)	6 STR- 350 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	6 AWG-350 kcmil

Physical

Installation Torque	275
Type of Plating	Tin
Connector Type	Terminal
Bolt Hole Size	1/2
Plated (Yes or No)	N
Product Material	Aluminum

Approvals / Certifications

Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Exempt
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175