

YCA30R2N

by Burndy
Catalog ID: YCA30R2N

Prop 65 Notice

AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 6.71 IN L



Product Details

General

Connector Type	Terminal
Die Index	251
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
UPC	781810810491
UPC 12 Digit	7818108104911

Dimensions

Dimension - B Length inch	2.57 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	170 mm
Dimension - Length Overall inch	6.71 in
Dimension - Outside Diameter inch	1.00 in
Dimension - Pad Width inch	1.42 in

Conductor Related

Conductor - ACSR Str Size	266.8 (18/1) Waxwing kcmil;266.8 (26/7) Owl kcmil;266.8 (26/7) Partridge kcmil
Conductor - ACSR Str Size Range	266.8 (18/1) Waxwing kcmil-266.8 (26/7) Partridge kcmil
Conductor - AL Str Size	266 kcmil
Conductor - AL Str Size Range	266 kcmil

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM

UL Listed	No
-----------	----

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)