



BURNDY Catalog Number
UPC Number
Description
Status

YA44LTC12FX
 7818100210644
 750FLEX 1/2STUD
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	3.79
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.33
B Length (in)	1.65
Pad Width (in)	2.19
Strip Length	1-5/8

General

Number of Holes	1
Product Description	Copper Compression Lug, 1 Hole w/ Inspection Window, 777.7 Flex, 1/2" Stud, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range	750
Flex (Class H) Size - Range	750
Flex (Class I) Size - Range	750
Copper Solid Size (Range)	N/A
DLO Size (Range)	777.7 (1925/#24)
Copper Stranded (Range)	N/A

Physical

Type of Plating	Tin
Bolt Hole Size	1/2
Color Code	Yellow
Plated (Yes or No)	Y
Index Number	L115
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175