Product data sheet Characteristics

26923

auxiliary contact - 1 OCS - 380..415 V - 6 A - for **RCCB**

Product availability: Stock - Normally stocked in distribution facility

Price* : 60.00 USD



Main

Wall	
Range	Multi 9
Product or component type	OC contact
Device short name	OFS
Signal contacts composition	1 C/O
[le] rated operational current	3 A at 380415 V AC - 50/60 Hz 6 A at 220240 V AC - 50/60 Hz 1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC
9 mm pitches	1

Complementary

B	M W O OFF OFF	÷
Range compatibility	Multi 9 GFP GFP	is to the state of
	Multi 9 C60 C60BP	. <u>v</u>
	Multi 9 C60 C60BPR	קר מי
	Multi 9 C60 C60SP	Į.
	Multi 9 C60H-DC C60H-DC	et i
Mounting mode	Fixed	substitute for
Mounting support	DIN rail	v v
Height	3.31 in (84 mm)	intended
Width	0.35 in (9 mm)	t inte
Depth	2.87 in (73 mm)	<u></u>
Connections - terminals	Clamp terminal 2 cable(s) 0 in ² (1.5 mm ²) flexible	docimentation
	Clamp terminal 2 cable(s) 0 in ² (1.5 mm ²) rigid	5
	Clamp terminal 1 cable(s) 00 in² (0.52.5 mm²) rigid	, and the second se
	Clamp terminal 1 cable(s) 0.52.5 mm² flexible	
Wire stripping length	0.35 in (9 mm)	
Tightening torque	8.85 lbf.in (1 N.m)	======================================

Environment

Standards	EN/IEC 60947-5-1
Product certifications	FIMKO SEMKO DEMKO
	NEMKO CEBEC
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 131 °F (55 °C)
Ambient air temperature for operation	-13122 °F (-2550 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)

Ordering and shipping details

0 11 0	
Category	01078 - DE2 MISC
Discount Schedule	DE2
GTIN	00785901930631
Nbr. of units in pkg.	1
Package weight(Lbs)	8.9999999999997E-2
Returnability	N
Country of origin	ES

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0716 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Contractadi Warranty		
Warranty period	18 months	