Product data sheet Characteristics

TSXCANCBDD3

CANopen cordset - molded female SUB-D9 connectors - standard - IP20 - UL - 3 m





| Range of product | CANopen |
|---------------------------------------|------------------------|
| Bus type | CANopen |
| Accessory / separate part category | Connection accessories |
| Accessory / separate part type | Connecting cable |
| Accessory / separate part destination | CANopen bus |
| Cable length | 9.84 ft (3 m) |
| | |

Complementary

| Electrical connection | 2 female connectors SUB-D 9 pin(s) |
|---------------------------------------|------------------------------------|
| Marking | CE |
| Product weight 0.59 lb(US) (0.268 kg) | |

Environment

| Product certifications | UL |
|-------------------------|------|
| IP degree of protection | IP20 |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------------|---|--|
| RoHS (date code: YYWW) | Compliant - since 1001 - Schneider Electric declaration of conformity | |
| | Schneider Electric declaration of conformity | |
| REACh | Reference not containing SVHC above the threshold | |
| | Reference not containing SVHC above the threshold | |
| Product environmental profile | Available | |
| | Product Environmental Profile | |
| Product end of life instructions | Need no specific recycling operations | |

| Product Life Status | END OF COMMERCIALIZATION |
|---------------------|--------------------------|
| Product Life Status | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |