



**POWER  
SYSTEMS, INC.**

**Interactive  
eCatalog**

*In the world of power transmission and distribution, look to Hubbell.*

[Catalog Home](#)

**Product Datasheet**

**CHANCE**

**W1040004 -- Grouted Rock Anchor**



Grouted  
Rock  
Anchor  
1.25"  
(31.7 mm)  
Diameter  
Rod 3'  
(914 mm)  
long (Guy  
Adapter  
ordered  
separately)

**Product Specifications**

Anchor Style

Rock Anchor

<b>Component</b>	Grouted
<b>Rod Diameter</b>	1.25" (31.7 mm)
<b>Length</b>	3' (914 mm)
<b>Rod Tensile Strength</b>	70,000 lbs (311.4 kN)
<b>Anchor Hole Size</b>	6" (152.4 mm)
<b>Coating</b>	Galvanized
<b>Material Type</b>	Non-Standard
<b>Standard Package</b>	1
<b>Standard Package Unit</b>	EA
<b>Min Order Qty</b>	1
<b>Weight / Ea.</b>	17.6 lbs
<b>Webpage</b>	Click <a href="#">HERE</a> to view the web page.
<b>Drawing</b>	Click <a href="#">HERE</a> to view drawing.

#### Notes

Caution: All components of the Chance anchoring system are performance mated. Use of other anchoring products or equipment will not necessarily produce the same results.

#### Compressed Product Number

W1040004

#### Strength Note

Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5° of alignment with the guy load may significantly lower strength. Recommended minimum installation depth is 12" in solid rock.

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.