



BURNDY Catalog Number
UPC Number
Description
Status

YAV27LTC38FX
7818100225111
CU-HYDENT 3/0 FLEX 3/8 S
Active

Web Use
BURNDY Product Line

Dimensional

Tongue Angle
Length (in)
Barrell Style
Bolt Hole Size (in)
Barrel Type
Thickness
B Length (in)
Pad Width (in)
Strip Length

Straight
2.34
Chamfered
0.39
Standard
0.14
1.00
1.03
1

General

Number of Holes
Product Description

1
Copper Compression Lug, 1 Hole
w/ Inspection Window, 3/0 Flex,
3/8" Stud, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range
Flex (Class H) Size - Range
Flex (Class I) Size - Range
Copper Solid Size (Range)
DLO Size (Range)
Copper Stranded (Range)

3/0 AWG
3/0 AWG
3/0 AWG
N/A
3/0 (450/#24) DLO
3/0 AWG

Physical

Type of Plating
Bolt Hole Size
Color Code
Plated (Yes or No)
Index Number
Product Material

Tin
3/8
Orange
Y
14
Copper

Approvals / Certifications

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS

Y
Y
Compliant
N
N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175