Powr-Reel™ with 3 Outlets

3-Conductor Grounded • Type SJO • 90°C • 300 Volts



CATALOG	NO. OF	AWG	LENGTH OF CORD	COLOR OF	PO	WER RA	TING	PKG. PER	WT./ UNIT LBS	WT./ CTN. LBS	UPC CODE
NUMBER	COND.	SIZE	(FT)	JACKET	VOLTS	AMPS	WATTS	CTN.			
44623.61.05	3	16	25	Yellow	125	10	1250	4	2.7	11	079407446230

Product Construction:

Conductor:

• 16 AWG stranded bare copper per ASTM B174

Insulation:

• Premium-grade, color-coded 90°C EPDM

Jacket:

- CPE; yellow
- Voltage rating: 300 volts

Applications:

· Shop tools

Features:

- Tangle-Proof® instant cord storage
- · Sturdy metal reel case
- Rubber cord
- 3 grounded outlets
- · Cord locks in place; pull on cord to engage retractable reel

Industry Approvals:

- UL Listed
- OSHA Acceptable

Plug-it[®] Ground Fault Circuit Interrupter (GFCI) and Surge Protector Plug



CATALOG NUMBER	PO VOLTS	WER RAT	PKG. PER CTN.	WT./ UNIT LBS	WT./ CTN. LBS	UPC CODE	
	VOLIG	Aiiii 0	WATTS	0114.		LDU	
D7524.13.05	125	15	1875	6	0.3	2	079407075249

Product Description:

The Plug-it® Ground Fault Circuit Interrupter and Surge Protector Plug detects power leaks and cuts off electricity in less than one second to prevent electric shock.

Product Construction:

Body:

• PVC; yellow

Applications:

• Use anywhere GFCI protection is desired: job sites, kitchens, bathrooms, garages and workshops

Features:

- · Detects power leaks and cuts electricity off in less than a second to prevent electric shock
- Test and reset buttons
- Use with any standard extension cord
- Use indoor or outdoor
- · Protects electrical circuitry from voltage fluctuations
- Maximum clamping voltage 790 volts
- MOV 80 joules

Industry Approvals:

- UL Listed
- OSHA Acceptable



