



**ATD2000C**

## Dual (Ultrasonic and Passive Infrared) Ceiling Sensors

Combines the excellent minor motion detection of ultrasonic with the outstanding passive infrared (PIR) long-range major motion detection.

Description	Voltage	Coverage Area	
		2000 sq. ft. (360°)	1000 sq. ft. (180°)
Low voltage sensor with photocell and isolated relay.	24V DC	<b>ATD2000CRP</b>	<b>ATD1000CRP</b>
Low voltage sensor.	24V DC	<b>ATD2000C</b>	—
Line voltage sensor.	120-277V AC	<b>ATD2000CL</b>	<b>ATD1000CL</b>

*Note: Low voltage ATD ceiling sensors must use a CU series control unit. See page E-10 for details. See pages E-25 to E-28 for technical specifications, coverage patterns and wiring schematics. For Assembled in USA units Add suffix "U"*



**ATD1000C**

## Ultrasonic Ceiling Sensors

Excellent minor motion detection.

Description	Voltage	Coverage Area	
		2000 sq. ft. (360°)	1000 sq. ft. (180°)
Low voltage sensor with photocell and isolated relay.	24V DC	<b>ATU2000CRP</b>	<b>ATU1000CRP</b>
Low voltage sensor.	24V DC	<b>ATU2000C</b>	—
Line voltage sensor.	120-277V AC	<b>ATU2000CL</b>	<b>ATU1000CL</b>

*Note: Low voltage ATU ceiling sensors must use a CU series control unit. See page E-10 for details. See pages E-25 to E-28 for technical specifications, coverage patterns and wiring schematics. For Assembled in USA units Add suffix "U"*



**ATU2000C**

## Passive Infrared Ceiling Sensors

Outstanding long range major motion detection.

Description	Voltage	Coverage Area
		1500 sq. ft. (360°)
Low voltage sensor with photocell and isolated relay.	24V DC	<b>ATP1500CRP</b>
Low voltage sensor.	24V DC	<b>ATP1500C</b>
Line voltage sensor.	120-277V AC	<b>ATP1500CL</b>

*Note: Low voltage ATP ceiling sensors must use a CU series control unit. See page E-10 for details. See pages E-25 to E-28 for technical specifications, coverage patterns and wiring schematics. For Assembled in USA units Add suffix "U"*



**ATU1000C**

## Low Profile, Line Voltage Passive Infrared Ceiling Sensors

Outstanding long range major motion detection in a compact low profile housing.

Voltage	Color	Load Rating	Coverage Area
			1500 sq. ft.
120-347V AC with photocell.	White	800W Inc., 1000W Fl. @ 120V AC 1800W Fluorescent @ 277V AC 2200W Fluorescent @ 347V AC	<b>LVPR1500R</b>



**ATP1500C**

## Ceiling Sensors Accessories

Description	Catalog Number
Ceiling sensor infrared, NEMA 4X enclosure.	<b>ACIPE*</b>
Ceiling mount raceway adapter.	<b>ACMRA</b>
Ceiling mount wire guard.	<b>ACMG</b>

*Note: \*Compatible with low voltage passive infrared sensors only.*



**ACIPE**



**ACMRA**



**ACMG**



**LVPR1500R**