

## SystemOne Flush Sub-Plates

Description	Catalog Number	Description	Catalog Number	Description	Catalog Number
<b>Style Line® Decorator/GFCI</b> (2) Style Line® decorator openings for power and/or datacom applications. (3) Non-Metallic (3.5) Metal	<b>S1SP</b>	<b>Duplex/Duplex</b> (2) Duplex openings for power and/or datacom applications. (3) Non-Metallic (3.5) Metal	<b>S1SPDU</b>	<b>Duplex/Style Line® Decorator</b> (1) Duplex and (1) Style Line® decorator opening for power and/or datacom applications. (3) Non-Metallic (3.5) Metal	<b>S1SPDUSL</b>
<b>Hubbell 4 X 4</b> (4) 20A, 125V receptacles. (4) Keystone openings for Hubbell jacks or flush AV connectors. Power can be wired as single or two circuit with isolated ground capability. (4) Includes  stickers. Provided with 15 ft. wire leads Provided with 30 ft. wire leads	<b>S1SP4X4</b> <b>S1SP4X4C</b> <b>S1SP4X415</b> <b>S1SP4X430</b>	<b>Carpet Furniture Feed Cover/Flange*</b> (1) 3/4" and (1) 1 1/2" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes carpet flange. (3) Non-Metallic Aluminum Fin. Brass Finish (3.5) Metal Black Gray	<b>S1SPFFAL</b> <b>S1SPFFBRS</b> <b>S1SPFFBL</b> <b>S1SPFFGY</b>	<b>Tile Furniture Feed Cover/Flange*</b> (1) 3/4" and (1) 1 1/2" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes tile flange. (3) Non-Metallic Aluminum Fin. Brass Finish (3.5) Metal Black Gray	<b>S1SPFFTAL</b> <b>S1SPFFTBR</b> <b>S1SPFFTBL</b> <b>S1SPFFTGY</b>
<b>Single Receptacle + Data</b> Opening for 20 or 30A Twist-Lock® receptacle (1.56" OD) and (2) Keystone openings for Hubbell jacks or flush AV connectors. (4)	<b>S1SPTL</b>	<b>Hubbell DataCom + Power</b> (1) 20A, 125V receptacle and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications. (5) Marked with " Controlled"	<b>S1SP3IM</b> <b>S1SP3IMC</b>	<b>Hubbell DataCom + Duplex</b> (1) Duplex opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. (5)	<b>S1SPDU2IM</b>
<b>Hubbell DataCom + Style Line® Decorator</b> (1) Style Line® decorator opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. (5)	<b>S1SPSL2IM</b>	<b>Hubbell DataCom</b> 1 unit flush Hubbell iSTATION opening and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications. (3.5)	<b>S1SP4IM</b>	<b>Active Multimedia + Power</b> Single 20A, 125V receptacle; (2) flush Keystone openings; (1) rectangular Style Line® decorator opening to accommodate active multimedia modules or low voltage outlet frames. (5) Marked with " Controlled"	<b>S1SPAMM20</b> <b>S1SPAMM20C</b>
<b>Extron® or FSR + Power</b> (1) 20A, 125V receptacle. Recessed opening for (3) single Extron® MAAP series adapter plates or FSR IPS plates. (4) Marked with " Controlled"	<b>S1SPEXT1</b> <b>S1SPEXT1C</b>	<b>Extron® or FSR + Power</b> (1) 20A, 125V receptacle. Recessed opening for (1) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates. (4) Marked with " Controlled"	<b>S1SPEXT2</b> <b>S1SPEXT2C</b>	<b>Extron® or FSR Single-Service</b> Recessed opening for (2) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates. (4.5)	<b>S1SPEXT3</b>
<b>Extron® AAP + Power</b> (1) 20A, 125V receptacle. (2) flush Keystone & recessed opening for (2) single Extron® AAP Series adapter plates. (4) Marked with " Controlled"	<b>S1SPEXT4</b> <b>S1SPEXT4C</b>	<b>Ortronics Series II® + Power</b> (1) 20A, 125V receptacle. Recessed opening for (3) 1 unit Ortronics Series II® modules. (5) Marked with " Controlled"	<b>S1SPORT</b> <b>S1SPORTC</b>	<b>Ortronics TracJack® + Power</b> (1) 20A, 125V receptacle. Recessed bezel for (6) Ortronics TracJack® modules. (5) Marked with " Controlled"	<b>S1SPTRAC</b> <b>S1SPTRACC</b>
<b>Panduit Mini Com® 4 X 4</b> (4) 20A, 125V receptacles. (4) Openings for Panduit Mini-Com Connectivity. (4) Includes  stickers.	<b>S1SP4X4PA</b> <b>S1SP4X4PAC</b>	<b>SYSTIMAX® 4 X 4</b> (4) 20A, 125V receptacles. (4) Openings for SYSTIMAX® Connectivity. (4) Includes  stickers.	<b>S1SP4X4SYS</b> <b>S1SP4X4SYS</b>	<b>Siemon MAX® + Power</b> (1) 20A, 125V receptacle. Recessed bezel for (6) Siemon MAX® modules. (5) Marked with " Controlled"	<b>S1SPMAX</b> <b>S1SPMAXC</b>

Note: \*Furnished with two screws in flexible metal conduit connectors.

⊖ Signifies minimum depth of concrete pour in inches for Metal Floor Boxes (**S1CFB**, **S1SFB** and **S1SFBV**) and Non-Metallic Floor Box (**S1PFB**).

## Sub-Plate Accessories

Description	Catalog Number	Description	Catalog Number
<b>Replacement Threaded Conduit Plugs</b> Used with <b>S1SPFFx</b> and <b>S1SPFFT</b> only. Sub-plate is supplied with plugs. 		Replacement for <b>S1SPMAX</b> . Sub-plate is supplied with data frame. Works with Siemon MAX®.	<b>S1DFMAX</b>
Color	1 1/2" Plug	Replacement for <b>S1SPTRAC</b> sub-plate. Sub-plate is supplied with data frame. Works with Ortronics TracJack®.	<b>S1DFTRAC</b>
Aluminum Finish	<b>S1FP15AL</b>	Blank Style Line® decorator frame, Black.	<b>NS620BK</b>
Brass Finish	<b>S1FP15BRS</b>	2-Port Style Line® decorator frame, Black.	<b>ISF2BK</b>
Black	<b>S1FP15BL</b>	4-Port Style Line® decorator frame, Black.	<b>ISF4BK</b>
Gray	<b>S1FP15GY</b>	6-Port Style Line® decorator frame, Black.	<b>ISF6BK</b>

Extron® is a registered trademark of Extron Electronics. MAX® is a registered trademark of The Siemon Company. Mini-Com® and Panduit® are registered trademarks of Panduit Corp. SYSTIMAX® is a registered trademark of CommScope, Inc. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.