

Product availability : Stock - Normally stocked in distribution facility



Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR and Switching Duty rated

Complementary

Line Rated Current	70 A
Poles description	3P
Breaking capacity	5 kA at: 48 V DC 10 kA at: 240 V AC
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
System Voltage	240 V AC 48 V DC
Mounting mode	Unit mount
AWG gauge	AWG 12...AWG 2/0 (aluminium/copper)
Height	4.05 in
Depth	2.95 in
Width	2.25 in

Environment

Product certifications	CSA IEC UL listed
------------------------	-------------------------

Ordering and shipping details

Category	00900 - QOU BREAKERS & SWITCH
----------	-------------------------------

Discount Schedule	DE2
GTIN	00785901060307
Nbr. of units in pkg.	1
Package weight(Lbs)	1.45
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------