Product data sheet Characteristics

9001SKT1R9 PILOT LIGHT 120VAC 30MM SK +OPTIONS

Product availability: Stock - Normally stocked in distribution facility



Price*: 197.00 USD



Main

Lens type	Domed plastic
Light block supply	Via transformer 110 V AC (f = 50/60 Hz) Via transformer 120 V AC (f = 50/60 Hz)

Complementary

Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	:
Shape of signaling unit head	Round	:
Operating mode	Push-to-test	

Environment

Protective treatment	TC
IP degree of protection	IP66

Ordering and shipping details

Category	21429 - 9001 SK,SKY	ute
Discount Schedule	CS1	
GTIN	00785901048534	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.4500000000000001	ini ini
Returnability	N	to a
Country of origin	MX	o <u>o</u>

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity	
	☑ Schneider Electric declaration of conformity	

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Contractual warranty	
Warranty period	18 months