Eaton BR1224L200R

Catalog Number: BR1224L200R

Eaton Eaton BR main lug loadcenter,No feed-thru lugs,includes BREQS125 hold-down screw, 200 A,B2R,Aluminum, NEMA 3R,Metallic,25 kAIC,BWH,NEMA 3R,24 Circuits,Twenty-four pole,12 Spaces,Three-wire,Single-phase,120/240V,#1 AWG-300 kcmil Cu/Al

General specifications



Eaton BR main lug loadcenter

UPC

786676447355

Product Height

18.75 in

Product Weight

15 lb

Certifications

UL 50 UL 67 Catalog Number

BR1224L200R

Product Length/Depth

5.19 in

Product Width

14.31 in

Warranty

10 year

Catalog Notes

Suitable for use as service equipment when no more than 6 main disconnecting means are provided or when not used as lighting & appliance panelboard. Has notch for brhdk125 hold-down kit.





Product specifications

Number of spaces

12

Special features

No feed-thru lugs, includes BREQS125 hold-down screw

Interrupt rating

25 kAIC

Phase

Single-phase

Wire size

#1 AWG-300 kcmil Cu/AI

Bus material

Aluminum

Main circuit breaker

BWH

Enclosure

NEMA 1

Amperage Rating

200 A

Enclosure material

Metallic

Type

Main lug

Cover

Cover included

Used with

Type BR 1-inch breakers

Number of wires

3

Number of circuits

24

Voltage rating

120/240V

Box size

B2R

Resources

Brochures

Loadcenters and Circuit Breakers

Type BR Arc Fault Circuit Breakers and Loadcenters

Catalogs

Eaton's Volume 1—Residential and Light Commercial

Drawings

Dimensional Drawing - BR 1 LOADCENTER, MAIN LUG ONLY, OUTDOOR NEMA 3R, 120/240 VAC, 1 PHASE

Installation instructions

Cutler-Hammer Type CH and BR Loadcenters - Instructions

Specifications and datasheets

Eaton Specification Sheet - BR1224L200R



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia