



Catalog # 232M

4 IN. SQUARE BOX, 2-1/8 IN. DEEP, WELDED, TEN 1/2 IN. KO'S AND SIX TKO'S

RAISED GROUND, 8 IN. #12 SOLID COPPER PIGTAIL, UBS, HM BRACKET

Square boxes are used where multiple conductor runs are split into two or more directions to bring power to a number of electrical devices. Built in bracket or supports speeds installation.

FEATURES

- UBS integrated support provides bracing on back of box for wall cavities between 2-1/2 In - 6 In. thickness,
- H/M Bracket
- Combination screw heads allow quick installation
- Welded construction
- Ten 1/2 In. knockouts and Six TKO knockouts
- 30.3 Cu. In. capacity
- Raised ground, 8 In. #12 Solid Copper pigtail
- Acceptable in 2-hour fire rated walls



APPLICATIONS

RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles

CERTIFICATIONS



SPECIFICATIONS

UPC NUMBER:	050169500040
EA LENGTH/DEPTH (IN.):	2.676
EA WIDTH (IN.):	5.86
EA HEIGHT (IN.):	4.03
WT. EA. (LBS.):	1.03
PACKAGE TYPE:	LOOSE
PRODUCT UPC-A LABELED:	NO

PACKAGING

CASE I2OF5:	50050169500045
STANDARD CARTON QTY:	25
MIN ORDER QTY:	25



All RACO single-gang, two-gang, 4 in. square, and single gang gangable U.L. listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult U.L. "Fire Resistance Directory" or the U.L. website at www.ul.com

600V Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

