# NSYS3DC3320



### Main

Range	Spacial
Product name	Spacial S3DC
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	11.81 in (300 mm)
Enclosure nominal width	11.81 in (300 mm)
Enclosure nominal depth	7.87 in (200 mm)
Door type	Plain
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory type	Wall-mounting
Device composition	Lock 1 Door 1 Body 1

# Complementary

Variant particularity	Gutter-shaped front profile double sheet thickness Single piece body	
Number of doors	1 front face	<del></del> .
Door opening side	Reversible 120 °	
Lock type	Screw driver insert lock	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Steel	;
Surface finish	Epoxy-polyester powder	
Colour	Grey RAL 7035	
Standards	IEC 62208	
Product certifications	UL	

### **Environment**

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

# Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1040 - Schneider Electric declaration of conformity	Compliant - since 1040 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

	···
Warranty period	18 months