

Vaporproof Lighting

Features:

- Durable die cast housing and guard for long product life
- Powder paint finish for corrosive environments
- Available in pendant, box and wall mounts
- Fixtures may be purchased complete or as components
- Fixtures constructed of die cast aluminum; screw-on guards are zinc die cast
- Heat-resistant clear globe available on 100 watt series
- Wire guard available

Certifications and Compliances:

- UL1598
- UL Listed File No. E-15625
- cUL Standard CSA C22.2 No 250.0
- Suitable for wet locations
- 100W max. incandescent series is UL approved for 27W max. SBCFL (equivalent to 100W incandescent)
- 200W max. incandescent series is UL approved for 42W max. SBCFL (equivalent to 200W incandescent)

Clear glass is standard; colors are available; plastic (polycarbonate) globes, which are virtually unbreakable, are available in colors and are used as an alternative to glass globe/guard combinations (not recommended to exceed 60 watts).

VAPORPROOF FIXTURES – GASKETED, CORROSION-RESISTANT DIE CAST CONSTRUCTION, GLASS GLOBES, DIE CAST GUARDS, UL LISTED



TP7600,
TP7601

TP7800,
TP7801,
TP7860

TP7610,
TP7611,
TP7805

TP7620,
TP7621

TP7810,
TP7811

TP7630,
TP7815

TP7640

TP7820

TP7650,
TP7825

Cat. #	Description	Hole Size	Incandescent Watts	SBCFL Watts	Std. Unit Carton	Wt. Lbs. Per 100
4" Box Mounted						
TP7600*	Clear Globe, Cast Guard	1/2"	100	27	1	325.0
TP7601	Clear Globe, Cast Guard	3/4"	100	27	1	324.0
TP7800	Clear Globe, Wire Guard	1/2"	200	42	1	516.7
TP7801	Clear Globe, Wire Guard	3/4"	200	42	1	516.0
TP7860	Fluorescent Clear Globe, Wire Guard	1/2"	13	-	1	413.0
TP7610	Clear Globe	1/2"	100	27	1	258.3
TP7611	Clear Globe	3/4"	100	27	1	258.0
TP7805	Clear Globe	1/2"	200	42	1	283.3
Pendant Mount						
TP7620	Clear Globe, Cast Guard	1/2"	100	27	1	300.0
TP7621	Clear Globe, Cast Guard	3/4"	100	27	1	299.0
TP7810	Clear Globe, Wire Guard	1/2"	200	42	1	350.0
TP7811	Clear Globe, Wire Guard	3/4"	200	42	1	349.0
TP7630	Clear Globe	1/2"	100	27	1	208.4
TP7815	Clear Globe	1/2"	200	42	1	258.4
Surface Mount, Fits 3" & 4" Round Boxes						
TP7640	Clear Globe, Cast Guard	-	100	27	1	275.0
TP7820	Clear Globe, Wire Guard	-	200	42	1	333.3
TP7650	Clear Globe	-	100	27	1	216.7
TP7825	Clear Globe	-	200	42	1	180.0

*Suitable for base-up applications.

Vaporproof

Vaporproof Lighting



TP7670, TP7835



TP7845

Cat. #	Description	Incandescent Watts	SBCFL Watts	Std. Unit Carton	Wt. Lbs. Per 100
Right Angle Bracket Fixtures					
TP7660	Clear Globe, Cast Guard	100	27	1	300.0
TP7830	Clear Globe, Wire Guard	200	42	1	516.7
TP7670	Clear Globe	100	27	1	200.0
TP7835	Clear Globe	200	42	1	400.0
Box Mounted					
TP7680	Clear Globe, Cast Guard	100	27	1	350.0
TP7840	Clear Globe, Wire Guard	200	42	1	560.0
TP7845	Clear Globe	200	42	1	450.0

VAPORPROOF COMPONENTS




Pendant



Ceiling Box Cap



Ceiling Box



Right Angle



Right Angle/Box

Cat. #	Description	Incandescent Watts	SBCFL Watts	Std. Unit Carton	Wt. Lbs. Per 100
Pendant Cap, Porcelain Socket, Gasket & Screws					
TP7496	Gray, 1/2"	100	27	10	18
TP7497	Gray, 3/4"	100	27	10	18
TP7498	Gray, 1/2"	200	42	10	10
TP7499	Gray, 3/4"	200	42	10	10
Ceiling Box Cap, Socket, Gasket & Screws					
TP7447	Gray	100	27	10	12
TP7479	Gray	200	42	10	12
Ceiling Mount Box with Gaskets, Porcelain Socket & Screws					
TP7450	Gray, 1/2"	100	27	10	19
TP7478	Gray, 3/4"	100	27	10	19
TP7451	Gray, 1/2"	200	42	10	19
TP7479	Gray, 3/4"	200	42	10	19
Right Angle Bracket, Gasket, Socket & Screws					
TP7445	Gray	100	27	10	21
TP7446	Gray	200	42	6	12
Right Angle Bracket, Attached Box, Gasket, Socket & Screws					
TP7440	Gray, 1/2"	100	27	1	3

Vaporproof

Vaporproof Lighting

VAPORPROOF FIXTURE ACCESSORIES



TP7460 - TP7466




TP7468 - TP7472



TP7474, TP7475









TP7476



TP7477

Cat. #	Description	Incandescent Watts	SBCFL Watts	Std. Unit Carton	Wt. Lbs. Per 100
TP7460	Glass Clear Globe, 130°F Max.	100	27	12	98.0
TP7462	Glass Amber Globe	100	27	12	120.0
TP7463	Glass Blue Globe	100	27	12	120.0
TP7464	Glass Green Globe	100	27	12	120.0
TP7466	Glass Clear Globe	200	42	6	200.0
TP7468	Lexan Clear Prismatic	75	-	12	58.4
TP7469	Lexan Blue Prismatic	60	-	12	58.4
TP7470	Lexan Red Prismatic	75	-	12	58.4
TP7471	Lexan Amber Prismatic	75	-	12	58.4
TP7472	Lexan White	75	-	12	58.4
TP7474	Bayonet Mount Die Cast Guard	100	27	12	108.4
TP7475	Wire Guard	200	42	6	183.4
TP7476	Clamp-on Wire Guard	100	27	12	62.5
TP7477	Adapter Plate	-	-	12	62.5

Dimensions (100 Watt):



Dimensions (200 Watt):

Cat. #	Length	Overall Width	Depth
TP7830	12 1/2"	5 1/2"	6 7/8"
TP7840	12 1/2"	5 1/2"	8"
TP7820	7 1/2"	4 1/2"	-
TP7810	11 1/2"	5 1/2"	-
TP7800	10 3/4"	5 1/2"	-

Photoelectric Lighting

PHOTOELECTRIC LIGHTING CONTROLS



TP7925



TP7927

Applications:

- Used for sunset activated automatic control of night lighting
- May be used to control outdoor lighting and signs

Features:

- Durable, weatherproof construction
- Built-in time delay prevents operation triggered by temporary light flashes

Cat. #	Description	Std. Unit Pkg.	Wt. Lbs. Per 100
TP7925	1200W Swivel Photocell, 120V	10	8.3
TP7927	300W Photocell, 120V	10	8.3