



Specifications

- 18 gauge cold rolled steel base
- White powder coat finish
- High impact thermoplastic ABS trim ring
- Ideal for new construction or renovation

Standards

- cULus 1863 listed
- UL V0 flame rating on ABS trim ring



①



②



③



④

FPTV Connection Enclosure

| Description | Height Inches (mm) | Width Inches (mm) | Depth Inches (mm) | Color | Catalog No. |
|---|--------------------|-------------------|-------------------|-------|------------------|
| 2-gang in-wall enclosure | 7.92" (201) | 8.16" (207) | 3.37" (86) | White | ① NSAV62M |
| 4-gang in-wall enclosure | 7.92" (201) | 14.80" (376) | 3.37" (86) | White | NSAV124M |
| Steel cover for NSAV62M | 7.2" (183) | 7.2" (183) | 0.05" (1) | White | ② NSAV6C |
| Steel cover for NSAV124M | 7.2" (183) | 13.80" (351) | 0.05" (1) | White | NSAV12C |
| Block wall adapter, compatible with NSAV62M | | | | | NSAV6BW |
| New work stud brackets | | | | | NSAV6NW |

Power Kits

| Description | Color | Catalog No. |
|---|-------|-----------------|
| Standard power kit; includes wallplate, box and 15A tamper-resistant outlet | White | NSOKPTR |
| Surge protected power kit; includes wallplate, box and surge protected outlet | White | ③ NSOKPS |

Feed-Through Wallplates

| Description | Color | Catalog No. |
|-------------|-------|-----------------|
| 1-gang | Ivory | ④ NSAV1I |
| | White | NSAV1W |
| 2-gang | Ivory | NSAV2I |