

### Standards

- ANSI/TIA-568.3
- TIA-604-FOCIS
- Telcordia GR-326-CORE

## Pre-Polished Connectors

900 μM cable, 10mm cleave length

### LC PROclick®

Color	Fiber Type	12-Pack	100-Pack
Aqua	50μM, OM3/OM4	① <b>FCLC900K50GM12</b>	<b>FCLC900K50GM100</b>
Beige	62.5μM, OM1	<b>FCLC900K62M12</b>	–
Black	50μM, OM2	<b>FCLC900K50M12</b>	–
Blue	SM, OS2	<b>FCLC900KSM12</b>	<b>FCLC900KSM100</b>



### SC PROclick®

Color	Fiber Type	12-Pack	100-Pack
Aqua	50μM, OM3/OM4	<b>FCSC900K50GM12</b>	<b>FCSC900K50GM100</b>
Beige	62.5μM, OM1	② <b>FCSC900K62M12</b>	–
Black	50μM, OM2	<b>FCSC900K50M12</b>	–
Blue	UPC SM, OS2	<b>FCSC900KSM12</b>	<b>FCSC900KSM100</b>
Green	APC SM, OS2	<b>FCSC900KASM12</b>	–



### ST 2Click®

Color	Fiber Type	12-Pack
Aqua	50μM, OM3/OM4	<b>FCST50GM12</b>
Beige	62.5μM, OM1	<b>FCST62M12</b>
Black	50μM, OM2	<b>FCST50M12</b>
Blue	SM, OS2	③ <b>FCSTSM12</b>



## PROclick® Fiber Tool Kit

### Description

Includes: cleave and strip tools, scissors, pocket visual fault locator, launch cord, adapter insert and bullet, clamp, work mat, cleaning fluid and wipes, safety glasses, case (see page G18 for more detail)

### Catalog No.

**OFPROKT1**



## Tools

### Description

Fiber Cleavers Multimode only, score and snap style  
SM or MM fiber, precision, with case

### Catalog No.

**OFCLV3**

④ **OFCLV5**

Visual fault locator (ST, SC, LC); use during termination for optimum test results

⑤ **OFVFLKT1**




## Four Easy Termination Steps



Strip



Wipe



Cleave



Insert and Click

Note: See color chart on page G2. For termination tools and accessories, see page G18. Cleave tool OFCLV3 suitable for multimode only. Visual Fault Locator OFVFLKT1 recommended during termination. Precision cleave tool OFCLV5 required for singlemode terminations. Use precision cleave tool for optimum performance.