



Compression Splice Uni-Grip®(One Die) Full Tension

by FARGO
Catalog ID: A151353

Compression Splice, Uni-Grip, Full Tension, for ACSR 1033.5 kcmil 45/7



* Representative image

Product Details

General

Compression Method	Uni-Grip (single die system)
Die Size	13CD
Material	Aluminum Alloy
Press Minimum	60 to
Tension Range	0 lb
UPC	096359277897

Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Diameter - Outside	1.213 in
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	23.4 in
Weight	4.616 lb

Electrical Ratings

Voltage Application	EHV; Standard
---------------------	---------------

Conductor Related

Conductor Compatibility	ACSR-Ortolan-1033.5-45/7
Conductor Diameter (Main) - Maximum	0 in
Conductor Diameter (Main) - Minimum	0 in
Conductor Type	ACSR
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

Certifications and Compliance

UL Listed	No
-----------	----

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscs@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com