


# Product Environmental Profile

## 9050JCK General Purpose Plug-in Timers



## Product overview

The 9050JCK General Purpose Plug-in Timers provide low-cost timing in a plug-in housing.

This range consists of: Types 9050JCK11 thru 9050JCK59 for variable time delay and types 9050JCK1F to 9050JCK5F for fixed time delay applications up to 7200 seconds of timing range. 9050JCK General Purpose Plug-in Timers are rated 10A @ 240V AC/30V DC, 1/2HP @ 120/240V AC (N.O.), 1/3HP @ 120/240V AC (N.C.), AC15/B300 (NO/NC), DC13/R300 (NO).

The representative product used for the analysis is 9050JCK13V20.


The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.

The environmental analysis was performed in conformity with ISO 14040.

## Constituent materials

The mass of the product range is from 98 g and 181 g including packaging. It is 113 g for the 9050JCK13V20.

The constituent materials are distributed as follows:



## Substance assessment

Products of this range are designed in conformity with the requirements of the European RoHS Directive 2011/65/EU and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

Details of ROHS and REACH substances information are available on the Schneider-Electric [Green Premium website](http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page) . (<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page> )

## Manufacturing

9050JCK General Purpose Plug-in Timers are manufactured at a production site which complies with the regulations governing industrial sites.

## Distribution

The weight and volume of the packaging have been optimized, based on the European Union's packaging directive. The 9050JCK General Purpose Plug-in Timers packaging weight is 17 g. It consists of Cardboard (16g), Paper and PET (1g).

## Use

The products of the 9050JCK General Purpose Plug-in Timers range do not generate environmental pollution (noise, emissions) requiring special precautionary measures in standard use.

The dissipated power depends on the conditions under which the product is implemented and used. This dissipated power is between 2 W and 3 W for the 9050JCK General Purpose Plug-in Timers product range. It is 2 W for the referenced 9050JCK13V20.

This thermal dissipation represents less than 0.08% of the power which passes through the product.

The 9050JCK General Purpose Plug-in Timers range does not need any maintenance operation.

## End of life

At end of life, the products in the 9050JCK General Purpose Plug-in Timers have been optimized to minimize the amount of waste and allow recovery of the product components and materials.

This product range doesn't need any special end-of-life treatment. According to countries' practices this product can enter the usual end-of-life treatment process.

The recyclability potential of the products has been evaluated using the "ECO DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

According to this method, the potential recyclability ratio is: 21%.

As described in the recyclability calculation method this ratio includes only metals, plastics and packaging material which have proven industrial recycling processes.

## Environmental impacts

Life cycle assessment has been performed on the following life cycle phases: Materials and Manufacturing (M), Distribution (D), Installation (I) Use (U), and End of life (E).

Modelling hypothesis and method:

- The calculation was performed on the 9050JCK13V20.
- Product packaging: is included
- Installation components: no special components included.
- Scenario for the Use phase: this product range is included in the category 1 Energy passing product: (assumed service life is 20 years and use scenario is: Product dissipation is 2W, loading rate is 100% and service uptime is 30%..

The electrical power model used for calculation is US model.

End of life impacts are based on a worst case transport distance to the recycling plant (1000km)

### Presentation of the product environmental impacts

Environmental indicators	Unit	For 9050JCK13V20					
		S = M + D + I + U + E	M	D	I	U	E
Air Acidification (AA for PEP)	kg H+ eq	1.27E-02	2.34E-04	1.76E-06	0.00	1.24E-02	1.47E-06
Air toxicity (AT for PEP)	m <sup>3</sup>	1.50E+07	3.14E+05	2.62E+03	0.00	1.47E+07	2.19E+03
Energy Depletion (ED for PEP)	MJ	9.72E+02	2.31E+01	1.31E-01	0.00	9.49E+02	1.05E-01
Global Warming Potential (GWP for PEP)	Kg CO <sub>2</sub> eq.	7.42E+01	1.20	9.31E-03	0.00	7.30E+01	7.48E-03
Hazardous Waste Production (HWP for PEP)	Kg	1.59	5.28E-02	1.15E-08	0.00	1.53	9.25E-09
Ozone Depletion Potential (ODP for PEP)	Kg CFC-11 eq.	1.44E-06	1.24E-07	1.75E-11	0.00	1.32E-06	1.42E-11
Photochemical Ozone Creation Potential (POCP for PEP)	Kg C <sub>2</sub> H <sub>4</sub> eq.	1.37E-02	4.98E-04	2.75E-06	0.00	1.32E-02	1.86E-06
Raw Material Depletion (RMD for PEP)	Y-1	1.29E-14	1.18E-14	1.89E-19	0.00	1.08E-15	1.53E-19
Water Depletion (WD for PEP)	dm <sup>3</sup>	1.36E+02	7.63	9.62E-04	0.00	1.29E+02	7.76E-04
Water Eutrophication (WE for PEP)	Kg PO <sub>4</sub> <sup>3-</sup> eq.	3.60E-04	1.26E-04	1.72E-08	0.00	2.34E-04	1.39E-08
Water Toxicity (WT for PEP)	m <sup>3</sup>	5.99	5.13E-01	3.96E-03	0.00	5.47	3.20E-03

Life cycle assessment has been performed with the EIME software (Environmental Impact and Management Explorer), version 5, and with its database version 2013-02.

The Use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators. According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range: Depending on the impact analysis, the environmental indicators (without RMD) of other products in this family may be proportional extrapolated by energy consumption values. For RMD, impact may be proportional extrapolated by mass of the product.

## System approach

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2011/65/EU of 8 June 2011), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

# Glossary

<b>Air Acidification (AA)</b>	The acid substances present in the atmosphere are carried by rain. A high level of acidity in the rain can cause damage to forests. The contribution of acidification is calculated using the acidification potentials of the substances concerned and is expressed in mode equivalent of H <sup>+</sup> .
<b>Air Toxicity (AT)</b>	This indicator represents the air toxicity in a human environment. It takes into account the usually accepted concentrations for several gases in the air and the quantity of gas released over the life cycle. The indication given corresponds to the air volume needed to dilute these gases down to acceptable concentrations.
<b>Energy Depletion (ED)</b>	This indicator gives the quantity of energy consumed, whether it is from fossil, hydroelectric, nuclear or other sources. It takes into account the energy from the material produced during combustion. It is expressed in MJ.
<b>Global Warming (GW)</b>	The global warming of the planet is the result of the increase in the greenhouse effect due to the sunlight reflected by the earth's surface being absorbed by certain gases known as "greenhouse-effect" gases. The effect is quantified in gram equivalent of CO <sub>2</sub> .
<b>Hazardous Waste Production (HWP)</b>	This indicator quantifies the quantity of specially treated waste created during all the life cycle phases (manufacturing, distribution and utilization). For example, special industrial waste in the manufacturing phase, waste associated with the production of electrical power, etc. It is expressed in kg.
<b>Ozone Depletion (OD)</b>	This indicator defines the contribution to the phenomenon of the disappearance of the stratospheric ozone layer due to the emission of certain specific gases. The effect is expressed in gram equivalent of CFC-11.
<b>Photochemical Ozone Creation (POC)</b>	This indicator quantifies the contribution to the "smog" phenomenon (the photochemical oxidation of certain gases which generates ozone) and is expressed in gram equivalent of ethylene (C <sub>2</sub> H <sub>4</sub> ).
<b>Raw Material Depletion (RMD)</b>	This indicator quantifies the consumption of raw materials during the life cycle of the product. It is expressed as the fraction of natural resources that disappear each year, with respect to all the annual reserves of the material.
<b>Water Depletion (WD)</b>	This indicator calculates the volume of water consumed, including drinking water and water from industrial sources. It is expressed in dm <sup>3</sup> .
<b>Water Eutrophication (WE)</b>	Eutrophication is a natural process defined as the enrichment in mineral salts of marine or lake waters or a process accelerated by human intervention, defined as the enrichment in nutritive elements (phosphorous compounds, nitrogen compounds and organic matter). This indicator represents the water eutrophication of lakes and marine waters by the release of specific substances in the effluents. It is expressed in grams equivalency of PO <sub>4</sub> <sup>3-</sup> (phosphate).
<b>Water Toxicity (WT)</b>	This indicator represents the water toxicity. It takes into account the usually accepted concentrations for several substances in water and the quantity of substances released over the life cycle. The indication given corresponds to the water volume needed to dilute these substances down to acceptable concentrations.

PEP achieved with Schneider-Electric TT01 V9 and TT02 V18 procedures in compliance with ISO14040 series standards

PEP in line with PEPecopassport PCR : PEP-PCR-ed 2.1-EN-2012 12 11

## Schneider Electric Industries SAS

35, rue Joseph Monier  
CS 30323  
F- 92506 Rueil Malmaison Cedex  
RCS Nanterre 954 503 439  
Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)