



Product Number: 64918

Order Abbreviation: MC100/U/ET23.5/942

General Description: METALARC POWERBALL 100W ceramic arc tube, 4200K, 94 CRI, reduced color shift, high performance, clear, pulse start, ET23.5, clear, enclosed rated, E 39 Mogul base.

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	MC100UET235942 20/CS 1/SKU
ANSI Code	C90/E
ANSI Code 2	C90/E
Approx. Lumens (initial - horizontal)	10000
Approx. Lumens (initial - vertical)	10000
Approx. Lumens (mean - vertical)	7000
Average Rated Life - Horizontal (hr)	24000
Average Rated Life - (hr)	24000
Base	E39 Mogul
Bulb	ET23.5
Color Rendering Index (CRI)	94
Color Temperature/CCT (K)	4200
Diameter (in)	2.953
Diameter (mm)	75.00
Family Brand Name	Metalarc® Powerball
Hot Restrike Time (min)	5-7
Lamp Finish	Clear
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	410
Maximum Bulb Temperature - Fahrenheit	752
Maximum Overall Length - MOL (mm)	197
Nominal Wattage (W)	100.00
Warm-up Time (min)	2-4

Footnotes

- Consult your LEDVANCE Lighting Representative for compatible electronic operating systems.
- Unjacketed reprographical/photochemical lamp.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaires. See lamp warning.
- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.