Product data sheet Characteristics

XB5RMA04 Pack SPS - XB5 - plastic handy box progammable receiver - 24..240 V AC/DC

Product availability : Stock - Normally stocked in distribution facility





Main

| 12 14 | 22 D4 27 | Discrimentation is not intended as a substitute for determining suitability of these modulestions |
|-----------------------------|---------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| | | |
| | | (|
| | | |
| Main | | 3 |
| Range of product | Harmony XB5R | |
| Product or component type | Wireless and batteryless package | |
| Device short name | XB5R | 4 |
| Head material | Plastic | 90 |
| Kit composition | 1 plastic push-button, 1 receiver and 1 set of caps | |
| Transmission frequency | 2405 MHz for transmitter | |
| | 2405 MHz for receiver | |
| Level or class | 5M00G7W | |
| Antenna type | Omnidirectional | |
| Device composition | ZBA79 | |
| | ZBRRA | |
| | ZB5AZ009 ZBRM01 | |
| | ZBSRZAO | |
| | ZBRT1 | - - - |
| | | |
| | | |
| Complementary | | |
| Control type | Wireless and batteryless push-button handy box assembled on fixing collar | |
| Type of receiver | Programmable receiver (2 relays) | 4 |
| [Us] rated supply voltage | 24240 V AC/DC 50/60 Hz | |
| Status LED | 1 LED green power ON | |
| | 2 LEDs green relay ON | 4 |
| | 2 LEDs green function mode | ţ |
| | 1 LED green and yellow reception signal | |
| Communication port protocol | Zigbee conforming to IEEE 802.15.4 | |
| Rated power in W | <= 1 mW | |
| Number of channels | 1 | |
| Modulation technique | O-QPSK | F |
| Bandwidth | 5 MHz | |
| | | |
| Sen 20, 2017 | | |

Complementary

| Control type | Wireless and batteryless push-button handy box assembled on fixing collar | |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------|--|
| Type of receiver | Programmable receiver (2 relays) | |
| [Us] rated supply voltage | 24240 V AC/DC 50/60 Hz | |
| Status LED | 1 LED green power ON 2 LEDs green relay ON 2 LEDs green function mode 1 LED green and yellow reception signal | |
| Communication port protocol | Zigbee conforming to IEEE 802.15.4 | |
| Rated power in W | <= 1 mW | |
| Number of channels | 1 | |
| Modulation technique | O-QPSK | |
| Bandwidth | 5 MHz | |



| Antenna | dain |
|---------|------|
| / | g |

Environment

| Environment | |
|------------------------|-----------------------------------------------------------------|
| Product certifications | UL C-Tick GOST CCC CSA |
| Marking | CE |
| Standards | UL 508 EN/IEC 60947-5-1 EN/IEC 60947-1 CSA C22.2 No 14 |
| Radio agreement | FCC RSS ARIB T66 ANATEL ICASA SRRC |

Ordering and shipping details

| Category | 22470 - XB5R WIRELESS PUSH BUTTON |
|-----------------------|-----------------------------------|
| Discount Schedule | I |
| GTIN | 00785901919452 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.660000000000003 |
| Returnability | Y |
| Country of origin | FR |

Offer Sustainability

| Green Premium product | |
|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compliant - since 1028 - Schneider Electric declaration of conformity | |
| Schneider Electric declaration of conformity | |
| Reference not containing SVHC above the threshold | |
| Reference not containing SVHC above the threshold | |
| Available | |
| Available | |
| | Compliant - since 1028 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold Available |

Contractual warranty

Warranty period

18 months