



GE
Lighting

74472 - GE240RS-MV-N

GE LFL Multi-Volt ProLine™ Electronic Program / Rapid Start Ballast

- High performance electronic ballast for all general fluorescent applications
- Multi-Voltage Technology handles voltage from 120 to 277V
- Light-weight, Low Profile Housing
- Parallel lamp operation means system maintenance is easier to manage



CAUTIONS & WARNINGS

GENERAL CHARACTERISTICS

Lamp Type	Fluorescent -
Bulb	Electronic
Ballast Type	Program / Rapid Start
Starting Method	Rapid start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal
Additional Info	Auto-restart/Thermally protected

ELECTRICAL CHARACTERISTICS

Supply Current Frequency	60.0 Hz
--------------------------	---------

DIMENSIONS

Weight	1.06 lb
Exit Type	
Remote Mounting Distance	18.0 ft
Remote Mounting Wire Gauge	18.0 AWG

PRODUCT INFORMATION

Product Code	74472
Description	GE240RS-MV-N
Standard Package	Case
Standard Package GTIN	10043168744727
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard	10
Package	
UPC	043168744720