



# Compression Splice VERSAtile™ Minimum Tension

by ANDERSON  
Catalog ID: VHS6

Prop 65 Notice

Copper long barrel Versatile splice, #6 STR

- For use with VersaCrimp or conventional die type tooling.



\* Representative image

## Product Details

### General

Application	Power Connector
Color Code	Blue
Compression Method	VersaCrimp or Conventional Die Tooling
Die Size	VC6-350, VC6350SN
Inhibitor Loaded	No
Material	Copper
Tension Range	0 lb
Trade Name	NO
UPC	096359338987
UPC 12 Digit	096359338987

### Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Dimension - L Length Overall mm	0 mm
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	2.38 in
Weight	0.049 lb

### Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600

### Conductor Related

Conductor Diameter (Conventional Tooling) - Maximum	0.184 in
Conductor Diameter (Conventional Tooling) - Minimum	0.184 in
Conductor Diameter (VersaCrimp) - Maximum	0.184 in
Conductor Diameter (VersaCrimp) - Minimum	0.184 in
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

### Certifications and Compliance

Certification - CSA Approved	Y
Certification - ETL	N
Certification - UL Recognized	N
Certification - cULus	N
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Logistics

Carton Quantity	450 EA
-----------------	--------

**For further technical assistance, please contact us**

### **Domestic Customer Service**

Hubbell Power Systems  
210 N. Allen Centralia, MO 65240 USA  
Phone: (573) 682-5521  
Fax: (573) 682-8475  
Email: [hpscsc@hubbell.com](mailto:hpscsc@hubbell.com)

### **International Customer Service**

Phone: +1-573-682-5521  
Fax: +1-573-682-8516  
Email: [hpsintlcs@hubbell.com](mailto:hpsintlcs@hubbell.com)