



Compression Splice VERSAtile™ Minimum Tension

by ANDERSON
Catalog ID: VHS1

Prop 65 Notice

Copper long barrel Versatile splice, #1 STR

- For use with VersaCrimp or conventional die type tooling.



* Representative image

Product Details

General

Application	Power Connector
Color Code	Green
Compression Method	VersaCrimp or Conventional Die Tooling
Die Size	VC6 (all), VC7 (all)
Inhibitor Loaded	No
Material	Copper
Tension Range	0 lb
Trade Name	NO
UPC	096359338833
UPC 12 Digit	096359338833

Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Dimension - L Length Overall mm	0 mm
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	2.88 in
Weight	0.098 lb

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600

Conductor Related

Conductor Diameter (Conventional Tooling) - Maximum	0.332 in
Conductor Diameter (Conventional Tooling) - Minimum	0.328 in
Conductor Diameter (VersaCrimp) - Maximum	0.332 in
Conductor Diameter (VersaCrimp) - Minimum	0.184 in
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

Certifications and Compliance

Certification - CSA Approved	Y
Certification - ETL	N
Certification - UL Recognized	N
Certification - cULus	N
Standards - RoHS Compliance Status	UI
UL Listed	Yes

Logistics

Carton Quantity	90 EA
-----------------	-------

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscsc@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com