



[Catalog Home](#)

Product Datasheet



ANDERSON FARGO

VHSS350 -- Versatile Splice



Copper short barrel Versatile splice

Product Specifications

<p>Splice Type</p>	 <p>VERSAtile™ Compression Splices (For use with Die type and VersaCrimp tools)</p>
<p>Versatile Compression Series</p>	 <p>VHSS Series Compression Splice VERSAtile™ Minimum Tension Copper Conductor</p>
<p>PDF Catalog Page</p>	<p>Click HERE to view the web page.</p>
<p>Conventional Tooling Conductor Size Minimum</p>	<p>0.675 in</p>
<p>Conventional Tooling Conductor Size Maximum</p>	<p>0.675 in</p>
<p>VersaCrimp Conductor Size Minimum</p>	<p>0.464 in</p>
<p>VersaCrimp Conductor Size Maximum</p>	<p>0.675 in</p>
<p>Material</p>	<p>Copper</p>
<p>Conventional Tooling Minimum Conductor</p>	<p>.675 in</p>
<p>Conventional Tooling Maximum Conductor</p>	<p>.675 in</p>
<p>Conventional Tooling Conductor Size</p>	<p>350 MCM</p>
<p>VersaCrimp Conductor Range</p>	<p>3/0-350 MCM</p>

VersaCrimp Conductor Minimum	.464 in
VersaCrimp Conductor Maximum	.675 in
Dimension D	1.12 in (29 mm)
Dimension L	2.38 in (60 mm)
Length before Compression	2.38 in (60 mm)
Compression Method	VersaCrimp or Conventional Die Tooling
Die Size	VC6-3, VC6FT, VC7, VC7FT
UL Listed	Yes
Inhibitor Loaded	No
Color Code	Red
Material Type	Non-Standard
UPC Code	09635933907
Standard Package	6
Standard Package Unit	Each
Min Order Qty	6
Weight / Ea.	0.196 lbs

Notes

For use with copper stranded conductor only.

Features

For use with VersaCrimp or conventional die type tooling.

Compressed Product Number

VHSS350

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.