

Interactive <u>Catalog</u>

ribution, look to Hubbell

Catalog Home

Product Datasheet ANDERSON FARGO

VHSS400 -- Versatile Splice



Copper short barrel Versatile splice

Prod			

Splice Type



VERSAtile™
Compression Splices
(For use with Die type
and VersaCrimp tools)

Versatile Compression Series



VHSS Series Compression Splice VERSAtileTM Minimum Tension Copper Conductor

	Copper Conductor	
PDF Catalog Page	Click HERE to view the web page.	
Conventional Tooling Conductor Size Minimum	0.726 in	
Conventional Tooling Conductor Size Maximum	0.728 in	
VersaCrimp Conductor Size Minimum	0.522 in	
VersaCrimp Conductor Size Maximum	0.728 in	
Material	Copper	
Conventional Tooling Minimum Conductor	.726 in	
Conventional Tooling Maximum Conductor	.728 in	
Conventional Tooling Conductor Size	400 MCM	
VersaCrimp Conductor Range	4/0-400 MCM	

VersaCrimp Conductor Minimum	.522 in	
VersaCrimp Conductor Maximum	.728 in	
Dimension D	1.19 in (30 mm)	
Dimension L	2.50 in (64 mm)	
Length before Compression	2.50 in (64 mm)	
Compression Method	VersaCrimp or Conventional Die Tooling	
Die Size	VC6-3, VC6FT, VC7, VC7FT	
UL Listed	Yes	
Inhibitor Loaded	No	
Color Code	Blue	
Material Type	Non-Standard	
UPC Code	09635933910	
Standard Package	6	
Standard Package Unit	Each	
Min Order Qty	6	
Weight / Ea.	0.294 lbs	

Notes

For use with copper stranded conductor only.

Features

For use with VersaCrimp or conventional die type tooling.

Compressed Product Number

VHSS400

Catalog Home



Warranty Info | **Trademarks** | **Terms of Use**

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.