



Pool & Spa: Mechanical Controls

T40604RT3 | Control System with Transformer and 300 W Load Center with T104M & T106M Mechanisms



T40604RT3

CONTROL SYSTEM WITH TRANSFORMER AND 300 W LOAD CENTER WITH T104M & T106M MECHANISMS

These mechanical control systems include built-in transformers for ease of installation.



Features & Applications

Features

- Load Centers have eight breaker spaces

Applications

- Low-Voltage Lighting

- All-in-one control power for pool/spa installation
- Easy to wire
- Can house additional Intermatic mechanisms and components
- Control two-speed pumps with the T40604RT3
- Heavy-duty Type 3R metal indoor/outdoor power and load center
- Wiring devices may be installed in these Load Centers with the use of Standoffs, sold separately
- Knockout on the side for additional wiring device

System Includes

System Includes (1)



T40000RT3

POOL/SPA TYPE 3R LOAD CENTER

Qty: 1

Specifications

Maximum ON/OFF Operations

0

Has Override Switch

No

Input Voltages Display

120/208/240 VAC, 60 Hz

Resistive

40 A, 120-240 VAC, 60 Hz

Inductive

40 A, 120-240 VAC, 60 Hz

Tungsten

40 A, 120-240 VAC, 60 Hz

Pilot Duty

1000 VA, 120-240 VAC, 60 Hz

Motor

2 HP, 24 FLA, 120 VAC, 60 Hz
5 HP, 28 FLA, 240 VAC, 60 Hz

Number of Trippers Included

0

Number of Circuits

2

Maximum Power Consumption (W)

3 W

Switch Type

1 NO/1 NC, DPST

Operating Temperature Max (°C)

54

Operating Temperature Max (F)

130

Operating Temperature Min (°C)

-40

Operating Temperature Min (F)

-40

Warranty

1-year

Related Accessories and Parts (7)



ET-NF

RC SNUBBER NOISE FILTER 24-277VAC/DC FOR ELECTRONIC CONTROLS



156T1978A

EXTRA/REPLACEMENT TRIPPERS 1 ON AND 1 OFF



21T156A

SPACER-STANDOFF, 3" LONG - 4 PACK




21T166A

SPACER-STANDOFF, 3" LONG - 2 PACK



WP1000C

PLASTIC IN-USE WEATHERPROOF COVER - SINGLE-GANG



124T1952

INSULATOR FOR DOUBLE-POLE TIME SWITCH (T103, T104, T105, T173, T174, T175, T176, T185, WH40)

124--00066

INSULATOR FOR 3-CIRCUIT TIMERS

