





No Hold




Hold

Standard Configuration

1 x SPST
Circuit

*See Note

1 x DPST
Circuits

FF Commercial Series Auto-Off Timers



- No electricity required to operate
- Replaces any standard single or multi-gang wall switch
- Automatically limits ON time for energy consuming loads
- Quick and easy installation
- Time-saving up-front terminal connection with teeter-type terminals
- Brushed metal finish switch plate meets NEC requirements

Hold† Single Pole Single Throw			No Hold Single Pole Single Throw			No Hold Single Pole Double Throw		
Model #	Time Cycle	Switch	Model #	Time Cycle	Switch	Model #	Time Cycle	Switch
FF5MH	5 Min.	SPST	FF5M	5 Min.	SPST	FF315M	15 Min.	*See Note
FF15MH	15 Min.	SPST	FF15MC	15 Min.	SPST	FF330M	30 Min.	*See Note
FF30MH	30 Min.	SPST	FF30MC	30 Min.	SPST	FF360M	60 Min.	*See Note
FF60MHC	60 Min.	SPST	FF60MC	60 Min.	SPST	FF32H	2 Hr.	*See Note
FF6HH	6 Hr.	SPST	FF2H	2 Hr.	SPST	FF34H	4 Hr.	*See Note
FF12HHC	12 Hr.	SPST	FF4H	4 Hr.	SPST	FF36H	6 Hr.	*See Note
FF32HH	2 Hr.	*See Note	FF6H	6 Hr.	SPST	FF312H	12 Hr.	*See Note
FF34HH	4 Hr.	*See Note	FF12HC	12 Hr.	SPST	No Hold Double Pole Single Throw		
FF312HH	12 Hr.	*See Note				Model #	Time Cycle	Switch
						FF415M	15 Min.	DPST
						FF430M	30 Min.	DPST
						FF460M	60 Min.	DPST
						FF46H	6 Hr.	DPST
						FF412H	12 Hr.	DPST

† Hold feature enables auto shut-off override

*1 x SPST N.O. connected to 1 x SPST N.C. Switch can be configured at 1 x SPDT by jumpering input terminals together

Replacement knob information see page 154.

Ratings:

Resistive (heater): 20 A, 125 VAC, 60 Hz, 10 A, 250/277 VAC, 60 Hz.

Tungsten (incandescent): 7 A, 125 VAC

Motor: 1 HP, 125 VAC, 60 Hz., 2 HP, 250 VAC, 60 Hz.

Warranty: Limited 1 year

Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly