Rittal - The System.

Faster – better – everywhere.

Door-Operated SwitchSZ 4127.010

Date: May 24, 2018



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Door-Operated Switch – SZ 4127.010

created: 24.05.2018 build on www.rittal.com/us-en



Drod	uct	daeci	ription
Prod	uct	aesci	HOHON

Version:	without connection cable
V CISIOII.	WILLIOUL COLLIGECTION CADIC

_			
Prod	luct	teatu	res

Rated	operating
voltag	e:

400 V

Installation options:

for LED System Light

for standard and courtesy lights without an integrated door-operated switch

For cooling units and air/water heat exchangers

For rated current (max.):

240 V AC, 6 A

Rated insulation voltage:

400 V AC

Rated impulse withstand voltage, phase to phase:

6000 V AC

Packaging unit:

1 pc(s).

Weight/packaging unit:

0.08 kg (0.2 lb.)

EAN:

4028177497740

Customs tariff number:

85365080

ETIM 6.0:

EC002626

© Rittal 2018

ETIM 5.0:	EC002626
e CI@ss 8.0/8.1:	27189266
e CI@ss 7.0/7.1:	27119116
eCl@ss 6.0/6.1:	27119116
eCl@ss 5.1/5.1.4:	27189241
Product description (long):	SZ Door-operated switch, with accessory for interior installation, without connection cable
Approvals	
Approvals:	CSA UL
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2018 2