



# 4300-NB



VIDEO

## Product Description

Four gang electrical box for use with nonmetallic sheathed cable

**Brand:** fiberglassBOX™  
**Catalog #:** 4300-NB

**Carton Quantity:** 18  
**Carton Weight:** 22 lb.

**Height:** 3-3/4 in.  
**Width:** 7-1/2 in.  
**Depth:** 3 in.  
**Volume:** 60 cu. in.  
**Type of Installation:** New Work  
**Wall Box**  
**Number of Gangs:** 4

**UPC:** 085339162704  
**UNSPSC:** 39121308  
**Country of Origin:** United States of America

## FEATURES

Machine tapped device holes, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps bulk packed

## APPLICATION

New work residential construction 2 HR fire resistive walls

## STANDARDS

ANSI / UL 514C: File No. E30594



## FIRE CLASSIFICATION

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

## COLOR

Beige/tan

## MATERIAL

Fiberglass reinforced polyester BMC

## MOUNTING

Angled mid nails with adjustable stabilizer bar

## ADDITIONAL MATERIALS

Carbon steel fasteners

Galvanized steel brackets and plated carbon steel fasteners

Polyvinyl chloride clamps