



BURNDY Catalog Number
UPC Number
Description
Status

YCS43R
 7818100150877
 605 AL JUMPER
 Active

Web Use
 BURNDY Product Line

B Length (Fraction)
 Length (in)
 B Length (in)
 Length (Fraction)

Dimensional

5-1/4
 10.62
 5.25
 10-5/8

General

Product Description

HYSPLICE AL sleeve with staked cable stop, designed to withstand jumper loop tensile and vibration stresses. ANSI C119.4 CLASS 2 (PARTIAL TENSION), 10-5/8 IN L Y

Prefilled (Oxide Inhibitor)

Conductor(s)

ACSR Size (Range)
 ACSR Compact Size (Range)
 AAAC 6201 Size (Range)
 Aluminum Size (Range)
 AAAC 5005-Size (Range)

605 (30/19) Teal kcmil-666.6
 (24/7) Flamingo kcmil
 N/A
 740.8 (37) kcmil
 636 kcmil
 740.8 (37) kcmil

Physical

Type of Splice
 Type of Plating
 Plated (Yes or No)
 Index Number
 Product Material

Jumper
 Unplated
 N
 292,319
 Aluminum

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

N
 N
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175