

YCS32

by Burndy
Catalog ID: YCS32

Prop 65 Notice

CU loop splice connector designed to withstand jumper loop tensile and vibration stresses up to 60 percentage RBS, Index: 209



Product Details

General

Connector Type	Splice
Die Index	209
Material	Copper
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Trade Name	HYSPLICE™
UPC	781810014264
UPC 12 Digit	7818100142644

Dimensions

Dimension - A Outside Diameter inch	1.24 in
Dimension - B Length fraction	2-64/81 in
Dimension - B Length inch	2.79 in
Dimension - B Outside Diameter inch	1.24 in
Dimension - L Length Overall mm	145 mm
Dimension - Length Overall inch	5.72 in

Conductor Related

Conductor - Copper Str Size	400 kcmil
Conductor - Copper Str Size Range	400 kcmil

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	10
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)