

# QO230EPD

## QO Miniature Circuit Breaker 30A 2P 120/240V 10kA Plug-in Mount

Product availability : Stock - Normally stocked in distribution facility



### Main

Product or component type	Miniature circuit-breaker
Range of product	QO
Line Rated Current	30 A
System Voltage	120/240 V AC
Mounting mode	Plug-in
Poles description	2P
Circuit breaker type	Ground fault protecting class B 30 mA
Circuit breaker application	Not rated
Electrical connection	Pressure plate

### Complementary

Breaking capacity	10 kA at: 120/240 V AC
Number of spaces required	2
AWG gauge	AWG 14...AWG 8 (copper) AWG 12...AWG 8 (aluminium)
Height	4.12 in
Depth	2.91 in
Width	1.5 in

### Environment

Product certifications	CSA UL listed
Ambient air temperature for operation	104 °F (40 °C)

### Ordering and shipping details

Category	00910 - QO-EPD,QOB-EPD BREAKERS
----------	---------------------------------

Discount Schedule	DE2A
GTIN	00785901120759
Nbr. of units in pkg.	1
Package weight(Lbs)	0.9500000000000007
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1340 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

### Contractual warranty

Warranty period	18 months
-----------------	-----------