

DIGITAL

Percentage & Cycle Timers

EJWT & ACT-MA Series



APPLICATIONS

- Poultry and livestock.
- Agriculture or greenhouse, oil well pumping.
- Ventilation, process control.
- Standards: Listed UL916.

FEATURES

- **EJWT — Percentage Timer**
 - 960 time combinations with two dials.
 - Cycle Time Dial sets 32 repeating cycles from 15 seconds to 24 hours.
 - Percentage ON Dial has 32 steps from 0% to 100%.
 - Repeats cycle as long as power is applied.
- **ACT — Cycle Timer**
 - 960 time combinations with two dials.
 - ON time dial sets 30 time steps from 30 seconds to 15.5 minutes.
 - OFF dial has 30 steps time steps from 30 seconds to 15.5 minutes.
 - Repeats cycle as long as power is applied.
 - Hold On or Hold Off positions included.
 - Standards: Listed UL916.

SPECIFICATIONS

- **Timing Accuracy:** 1% of timing range.
- **Terminal Range:** #12 - #18AWG.
- **Operating Temperature:** 32°F to +122°F (0°C to + 50°C).
- **Power Consumption:** 16VA Max.
- **Enclosure:**
 - Indoor NEMA 4X is standard. (See Pages 464-468 For Dimensions).

WIRING DIAGRAMS

- See Pages 377-388 For Diagrams.

ACT30MA



CAT. NO.	UPC CODE	INPUT SUPPLY (VAC) 50/60Hz	OUTPUT CONTACTS
EJWT	82513	120-240	SPDT
ACT30MA	82527	120-240	SPDT

TYPE	VOLTAGE (VAC)	RATING	
		NO	NC
General Purpose	120-240	20A	10A
Resistive	120-240	20A	10A
Motor	120	1.5HP	1/4HP
	208-240	3HP	1/2HP
Pilot Duty	120/240	470VA	275VA