# Eaton FCF20RN

Bussmann

**UPS/CRITICAL** 

**Applications** 

FCF20RN€

# Catalog Number: FCF20RN

Eaton Bussmann series FCF fuse, 20 A, 60 Hz, 50 Hz, 1, CF, Black, Non-indicating, Electroless tin plated copper alloy terminal, Blade end|Class CF, 4 min at 200%, 300 kAIC at 600 V|50 kAIC at 600 Vdc, Glass filled PES, 600 Vdc

### General specifications



Eaton Bussmann series FCF fuse

**UPC** 

051712362467

Product Height

1.75 in

**Product Weight** 

0.08 lb

Compliances

CE Marked RoHS Compliant Catalog Number

FCF20RN

Product Length/Depth

1.88 in

Product Width

0.75 in

Warranty

Not Applicable

Certifications

UL Listed
CSA Certified



# Electrical rating

Amperage Rating

20 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

300 kAIC at 600 Vac 50 kAIC at 600 Vdc

Response time

4 min at 200%

Voltage rating

600 Vac, 600 Vdc

# Physical details

Color

Black

Fuse type

Class CF

Fast acting

Material

Glass filled PES

Number of elements

1

**Operating Temperature** 

-40° to 80°C

Packaging type

Standard

Terminal material

Electroless tin plated copper alloy terminal

### General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Special features

Superior overload and cycling capabilities

Used with

TCFH30N, CCP2-3-30CF

#### Resources

Catalogs

FCF20RN~Fast Acting CUBEFuse 20A Non-indication

Bussmann series complete full line catalog no. 1007

Multimedia

The Power of Space

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - FCF20RN



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia