

Technical data sheet

Flexible Control and Tray Cable TRAY-ER PVC · Unshielded

LUTZE SILFLEX® N Control Cable PVC For Stationary Applications



Identification

Type SI N TRAY-ER 4×AWG20 GR
Part No. [A3082004](#)

Product version

Datasheet version 00

Use/Application/Properties

- Application
- Multi-wire control cables with TC-ER „Exposed Run“ approval
 - Machine tools, machine and plant construction, VAC technology as well as other uses.
 - Compliant with NFPA 79 requirements
 - TC-ER-JP for use with cable trays without conduit, which can reduce installation costs in industrial environments
 - WTTC – wind turbine tray cable rating for use in wind power generation
 - PLTC-ER Power Limited Tray Cable – Exposed Run
 - ITC-ER Instrumentation Tray Cable
 - Dry, damp or wet locations
- Properties
- Crush impact resistant
 - Gas/vapor-tight sheath per UL 1277
 - Non-wicking fillers
 - Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures
 - Sunlight resistant
 - Flame-retardant
 - Direct burial (AWG 18 and larger)
 - Talc free and silicone free

Construction

Description SILFLEX® CONTROL CABLE PVC
Number of conductors/cross-section 4×AWG20
Number of conductors 4
Cross-section, metric 0.5 mm²

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

23.06.2023 • Subject to technical modification

Part No. [A3082004](#) • Datasheet version: 00

page 1 of 3

Technical data sheet

Flexible Control and Tray Cable TRAY-ER PVC · Unshielded

Cross-section AWG	AWG 20
Jacket material	PVC
Jacket color	grey similar to RAL 7001
Outer Ø	7.3 mm
Outer Ø	0.287 inch
Weight	7.3 kg/100 m
Weight	49 Lbs/Mft
Cu-Index	1.9 kg/100 m
Cu-Index	13 Lbs/Mft

Construction Element 1

Element construction	AWG20/4C
Conductor construction	AWG 20 (10/30)
Conductor	AWG conductor CU-wire bare
Conductor category	fine wire Class K
Conductor marking	black · with white number print · green/yellow
Conductor insulation	PVC/Nylon THHN – THWN

Overall construction

Jacket characteristics	Oil resistant Silicone-free
------------------------	--------------------------------

Technical data

Rated voltage U_N	300 V 90 °C PLTC-ER 300 V ITEC-ER 600 V UL MTW Cable, 1000 V 105C AWM
Temperature range fixed	+90 °C ... +105 °C
Minimum bending radius fixed	4×D

Technical Data Element 1

Element construction	AWG20/4C
----------------------	----------

Certifications/Standards

Certifications	UL Type MTW or DP-1 Meets NEC 336, 392, 725, 727 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 C(UL) TC and CIC FT4 UL 1277 PLTC-ER ITC-ER
UL style	AWM 20886

Technical data sheet

Flexible Control and Tray Cable TRAY-ER PVC · Unshielded

Conformity	CE RoHS REACH TSCA
Oil resistant according to	Oil Res II

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--