

**Product Number:** 25037

**Order Abbreviation:** F96T12/941/HO/SS/ECO

**General Description:** 95W, 96 inch MOL, T12 HO (800mA) rapid start SUPERSAVER fluorescent lamp, 4100K color temperature, 88 CRI. VIVID Color: High CRI lamps for color critical applications.



**\* Full Case Required**

### Product Information

Abbrev. With Packaging Info.	F96T12941HOSSECO 15/CS 1/SKU
Actual Length (in)	93.909
Actual Length (mm)	2385.29
Average Rated Life (hr)	12000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	88
Color Temperature/CCT (K)	4100
Diameter (in)	1.593
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	8000
Mean Lumens at 25C	7600
Nominal Length (in)	96.000
Nominal Length (mm)	2438.40
Nominal Wattage (W)	95.00
Outside Diameter (in)	1.593
Life at 3 hrs./start on IS ballasts	15000
Life at 12 hrs./start on IS ballasts	23500



### Footnotes

- Recommended for use on one or two lamp high power factor, lead, 8-foot lamp, high output, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low powerfactor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 95 watt lamps.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.