

QOM2150VH

QO Primary Main Breaker 150A 2P 120/240V 22kA Bolt-on Mount

Product availability : Stock - Normally stocked in distribution facility



Main

Product or component type	Circuit breaker
Range of product	QO
Line Rated Current	150 A
System Voltage	120/240 V AC
Mounting mode	Bolt-on
Poles description	2P
Circuit breaker type	Standard
Electrical connection	Lugs
Device short name	QOM2

Complementary

Breaking capacity	22 kA at: 120/240 V AC
AWG gauge	AWG 4...300 kcmil (aluminium/copper)
Height	5.6 in
Depth	5.07 in
Width	3.6 in
Load center type	Main breaker
Phase	1 phase
Product destination	QO load center Homeline load center

Environment

Product certifications	IEC CSA
Ambient air temperature for operation	104 °F (40 °C)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Ordering and shipping details

Category	00100 - QOM-VH MAIN CB
Discount Schedule	DE3A
GTIN	00785901004059
Nbr. of units in pkg.	1
Package weight(Lbs)	2.5699999999999998
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1411 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------