



Color: N/A

White, Ivory, Light Almond

UPC Code: 07847757043
Country Of Origin: China

# **IPVD6-1LZ**

#### **Brand Features**

Leviton's IPVD6/IPSD6 Universal Vacancy and Occupancy Sensors combine state-of-the-art technology with new aesthetics to provide optimal management of lighting and motor loads and a choice of either Manual-ON (Vacancy Sensor) or Automatic-ON (Occupancy Sensor) switching. These energy-saving sensors are engineered to control current LED, CFL and incandescent loads and ensure that lights/motors will turn ON manually (vacancy) or automatically (occupancy) and turn OFF automatically when motion is no longer detected within the covered range. Designed to fit in a standard wallbox, both devices offer 180° Field of View and 900 sq. ft. of coverage. All models have screw terminals for easy installation and do not require a neutral wire for connection. The devices feature a time delay setting which allows users the option to delay the lights/motor load from switching off for 30 seconds, 5 minutes, 15 minutes or 30 minutes. For example, closet lighting would ideally be set to turn OFF in 30 seconds while a bathroom fan may be set to turn OFF 15 minutes after the space is vacated.

The IPVD6/IPSD6 is a dimming sensor, featuring the ability for users to easily adjust lighting levels of compatible dimmable LED, dimmable CFL and Incandescent lamps for energy-efficiency and ambiance. A built-in advanced starting technology ensures smooth start-up for hard to start CFLs.

## **Item Description**

Vacancy detector and dimmer, 180 Degree PIR Wall Box Sensor, Single Pole &3-Way, 600 Watt Incandescent, 150W Dimmable LED &CFL. White assembled on the device, ivory and light almond color change kit included. Wall Plate Not Included.

#### **Features and Benefits**

- Universal Light Control & Dimmer Easily Switches Incandescent and Dimmable CFL, LED bulbs
- Manual-ON/Automatic OFF operation for seamless energy management
- Can be used to comply with 2016 California Title 24, Part 6 Vacancy Control Device Requirements
- Single Pole or 3 Way when used with a standard 3-way switch
- Low-Profile design eliminates an obtrusive "scanning device" look. Elegant styling compliments any interior and coordinates with Leviton's popular line of Decora® wiring devices
- 180 degree field-of-view provides approximately 900 square feet of coverage suitable for bathrooms, basements, garages, utility rooms and a variety of other residential areas
- Convenient push-button provides Manual OFF light switching at any time
- Segmented lens provides optimum sensitivity and performance. It is designed
  with an extensive "minor motion" area where even slight body movements will be
  detected
- Four optional manual adjustments for delayed-OFF time settings maximize energy savings: 30 seconds (for walking test), 10 minutes, 20 minutes and 30 minutes
- LED Indicator Light flashes when sensor detects motion to verify detection is active
- Fits in standard wallbox and replaces single-pole wall switch
- Neutral wire not required, suitable for retrofit and new construction applications
- Five-Year Limited warranty

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$ 

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

# Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

#### Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

# Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

