



**Product Number:** 64969

**Order Abbreviation:** MC70T6/U/G12/830

**General Description:** METALARC POWERBALL 70W ceramic metal halide tubular T6, clear, universal operation, G12 base, 3000K CCT, 87 CRI, pulse start, enclosed rated, 15 ,000 hour rated life

#### Product Information

Abbrev. With Packaging Info.	MC70T6UG12830 12/CS 1/SKU
ANSI Code	C139/E
ANSI Code 2	C139/E
Approx. Lumens (initial - horizontal)	7400
Approx. Lumens (initial - vertical)	7000
Approx. Lumens (mean - horizontal)	5600
Approx. Lumens (mean - vertical)	5600
Arc Length (in)	0.29
Arc Length (mm)	7.4
Base	G12
Bulb	T6
Color Rendering Index (CRI)	89
Color Temperature/CCT (K)	3000
Diameter (in)	0.748
Diameter (mm)	19.00
Family Brand Name	POWERBALL® CERAMIC METALARC® TUBULAR SINGLE-ENDED
Fixture Requirement	E
Hot Restrike Time (min)	2-15
Light Center Length - LCL (in)	2.2
Light Center Length - LCL (mm)	56
Maximum Base Temperature - Fahrenheit	536
Maximum Bulb Temperature - Fahrenheit	932
Maximum Overall Length - MOL (in)	3.94
Maximum Overall Length - MOL (mm)	100
Nominal Voltage (V)	95.00
Nominal Wattage (W)	70.00
Operating Position	Universal
Warm-up Time (min)	2-4

#### Footnotes

- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.

