

# YCA2R2N

by Burndy  
Catalog ID: YCA2R2N

Prop 65 Notice

AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 5.90 IN L

Features: Compression Terminal, Conductor Type: ACSR/6201/5005 (Compressed/Compact), Aluminum, Tools, Die Set Catalog Number, And (number Of Crimps): MD6, MD7 Tool, W239 Die, (3), Y35, Y750 Tool, U239 Die, (2), Y45 Tool, U239 Die With PT-6515 Adapter, (2), Y46 Tool, U239 Die With PUADP-1 Adapter, (2), Die Index: 239

## Product Details

### General

Application	For ACSR/6201/5005 (Compressed/Compact), Aluminum
Connector Type	Terminal
Construction Material - Main	Aluminum
Die Index	239
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	Terminals, TERMINAL
Type	YCA-R-N, Terminal
UPC	781810016633
UPC 12 Digit	7818100166333

### Dimensions

Dimension - B Length inch	1.61 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	149 mm
Dimension - Length Overall inch	5.90 in
Dimension - Outside Diameter inch	0.52 in
Dimension - Pad Width inch	1.25 in

### Conductor Related

Conductor - ACSR Str Size	2 (6/1) Sparrow AWG
Conductor - ACSR Str Size Range	2 (6/1) Sparrow AWG
Conductor - AL Str Size	2 AWG
Conductor - AL Str Size Range	2 AWG

### Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	25
-----------------------	----

For further technical assistance, please contact us

**BURNDY Headquarters**  
47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**  
8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)