

## **DESCRIPTION**

The CEL Series offers quality and value with an Edge-Lit LED based emergency exit. The CEL is ideal for architectural applications and offers surface and recessed mounting options. The acrylic panels are ultrasonically welded and taped at the edges to maximize illumination and visibility. The Exit panel can be ratcheted to various angles for mounting to angled surfaces. The housing finish and trim-plate is brushed aluminum. Recessed mount model comes with a full recessed box complete with integrated caddy-bar assembly. Surface mount model has a clam-shell design for easy installation and access to internal circuitry. Canopy and mounting hardware included. Models are available with AC only or Emergency with Nickel Cadmium battery, status LED and Push-to-Test switch.

#### **APPLICATION**

The CEL Series is applied in stairwells, hallways, offices and other commercial applications.

## **COMPLIANCES**

Listed to UL924 Standard NFPA 101 and NFPA 70 OSHA

#### WARRANTY

2 year full unit warranty





**Recessed Mount Wall or Ceiling** 



### **FEATURES**

Surface Mount

- · Superior panel illumination with Red or Green letters
- LED life-cycle of more than 10 years
- Dual-voltage 120 or 277V AC input
- Low Input Power Consumption at 3.72 Watts
- Emergency Models include long-life Nickel Cadmium battery for UL recognized 90 minute emergency lighting
- Field installed directional arrow indicators with template
- Mirror divider on single and double-face models
- Emergency Model provided with test switch and AC-On indicator
- · Canopy included for surface mount model

# **ORDERING GUIDE**

| Catalog Number | Description   |
|----------------|---|
| CELS1RNE       | Surface Mount, Single Face, Red Letters, Brushed Aluminum with Battery    |
| CELS1GNE       | Surface Mount, Single Face, Green Letters, Brushed Aluminum with Battery  |
| CELS2RNE       | Surface Mount, Double Face, Red Letters, Brushed Aluminum with Battery    |
| CELS2GNE       | Surface Mount, Double Face, Green Letters, Brushed Aluminum with Battery  |
| CELS1RN        | Surface Mount, Single Face, Red Letters, Brushed Aluminum, AC only        |
| CELS2RN        | Surface Mount, Double Face, Red Letters, Brushed Aluminum, AC only        |
| CELS1GN        | Surface Mount, Single Face, Green Letters, Brushed Aluminum, AC only      |
| CELS2GN        | Surface Mount, Double Face, Green Letters, Brushed Aluminum, AC only      |
| CELR1RNE       | Recessed Mount, Single Face, Red Letters, Brushed Aluminum with Battery   |
| CELR1GNE       | Recessed Mount, Single Face, Green Letters, Brushed Aluminum with Battery |
| CELR2RNE       | Recessed Mount, Double Face, Red Letters, Brushed Aluminum with Battery   |
| CELR2GNE       | Recessed Mount, Double Face, Green Letters, Brushed Aluminum with Battery |
| CELR1RN        | Recessed Mount, Single Face, Red Letters, Brushed Aluminum, AC only       |
| CELR2RN        | Recessed Mount, Double Face, Red Letters, Brushed Aluminum, AC only       |
| CELR1GN        | Recessed Mount, Single Face, Green Letters, Brushed Aluminum, AC only     |
| CELR2GN        | Recessed Mount, Double Face, Green Letters, Brushed Aluminum, AC only     |





## **DIMENSIONS**







