

Eaton FCF6RN

Catalog Number: FCF6RN

Eaton Bussmann series FCF fuse, 6 A, 60 Hz, 50 Hz, 1, CF, Black, Non-indicating, Electroless tin plated copper alloy terminal, Blade end, 4 min at 200%, 50 kAIC at 600 Vdc|300 kAIC at 600 V, Glass filled PES, Standard, 600 Vdc



General specifications

Product Name	Catalog Number
Eaton Bussmann series FCF fuse	FCF6RN
UPC	Product Length/Depth
051712362436	1.88 in
Product Height	Product Width
1.75 in	0.75 in
Product Weight	Warranty
0.08 lb	Not Applicable
Compliances	Certifications
CE Marked	UL Listed
RoHS Compliant	CSA Certified

Electrical rating

Amperage Rating

6 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

300 kAIC at 600 Vac

50 kAIC at 600 Vdc

Response time

4 min at 200%

Voltage rating

600 Vac, 600 Vdc

Physical details

Color

Black

Fuse type

Fast acting

Class CF

Material

Glass filled PES

Number of elements

1

Operating Temperature

-40° to 80°C

Packaging type

Standard

Terminal material

Electroless tin plated copper alloy terminal

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Special features

Superior overload and cycling capabilities

Used with

TCFH30N, CCP2-3-30CF

Resources

Catalogs

FCF6RN~Fast Acting CUBEFuse 6A Non-indication

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

The Power of Space

Specifications and datasheets

Eaton Specification Sheet - FCF6RN



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)