



* Representative image

35 kV, Load Break Elbow w/ Test Point, Bimetal Contact

by Hubbell Power Systems
Catalog ID: 236LE55T

Load Break Elbow, 200 Amp, 35 kV, with Test Point, Long Bimetal Contact, Cable Insulation Diameter range = 1.020 - 1.310 inches, 2/0 Solid or Compacted and 1/0 Stranded or Compressed

Product Details

General

Connector Type	Bi-Metal
PROBELOK [®] Connectors	No
Type	200Amp Load Break
UPC	096359530039
With Seal Kit	No
With Test Point	Yes

Dimensions

Cable Insulation Diameter Maximum	1.310 in
Cable Insulation Diameter Minimum	1.020 in
Weight	5.500 lb

Electrical Ratings

AC Withstand Voltage (1 min)	50 kV
Basic Impulse Level	150 kV
Corona Extinction (3pC)	26 kV
Current Rating	200 A
kV Class	35 kV

Conductor Related

Cable Insulation Diameter Range	1.020 - 1.310
Solid or Compacted Conductor	2/0
Stranded or Compressed Conductor	1/0

Logistics

Pallet Quantity	108 EA
Standard Package	20

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscshubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com