



BURNDY Catalog Number
UPC Number
Description
Status

YA34LNT12
 7818102702199
 500, SHORT, 1/2,NAR.TONG
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle Straight
 Length (in) 3.65
 Bolt Hole Size (in) 0.52
 Barrel Type Standard
 Thickness 0.23
 B Length (in) 1.27
 Pad Width (in) 0.96
 Strip Length 1-7/16

General

Number of Holes 1
 Product Description Copper Compression Lug, Narrow Tongue, 1 Hole w/ Inspection Window, 500 kcmil, 1/2" Stud, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range N/A
 Flex (Class H) Size - Range N/A
 Flex (Class I) Size - Range N/A
 Copper Solid Size (Range) N/A
 DLO Size (Range) N/A
 Copper Stranded (Range) 500 kcmil

Physical

Type of Plating Tin - Electro Plated
 Bolt Hole Size 1/2
 Color Code Brown
 Plated (Yes or No) Y
 Index Number 20
 Product Material Copper

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175