

# PHILIPS

## Lighting



# Energy Advantage IR PAR38

## Energy Advantage IR 83PAR38/IRC+/FL25 120V 12/1


Due to the heat that radiates from the bulb, a minimum distance of 2 ft is required between bulb and combustible materials or objects susceptible to drying or fading

### Product data

General Information		Cap-Base Information	
Cap-Base	E26/50X39 [ Skirted Medium Screw (PAR Lamps)]	Cap-Base Information	Brass [ Brass Cap]
Operating Position	Universal [ Universal]	Bulb Material	Hard Glass
Main Application	Flood and Ambient Lighting	Reflector Finish	Aluminized
Gas Filling	GAS	Filament Shape	CC-8 [ Axial]
Life with 3 Hour Per Day Use	3.8 a	<b>Approval and Application</b>	
<b>Light Technical</b>		Estimated Energy Cost Per Year	10.00 \$
Beam Angle (Nom)	25 °	<b>Product Data</b>	
Initial lumen (Nom)	1750 lm	Order product name	Energy Advantage IR 83PAR38/IRC+/FL25 120V 12/1
Luminous Intensity (Nom)	7000 cd	EAN/UPC - Product	046677238513
Beam Description	Flood [ Flood]	Order code	238519
Correlated Color Temperature (Nom)	2730 K	Numerator - Quantity Per Pack	1
Color Rendering Index (Nom)	100	Numerator - Packs per outer box	12
<b>Operating and Electrical</b>		Material Nr. (12NC)	924757133901
Power (Rated) (Nom)	83 W	Net Weight (Piece)	370.000 g
Voltage (Nom)	120 V		
<b>Mechanical and Housing</b>			
Bulb Finish	Clear (CL)		

## Energy Advantage IR PAR38

### Dimensional drawing



Product	D	C (max)
Energy Advantage IR 83PAR38/IRC+/FL25 120V 12/1	4.75 in	5.313 in

PAR38 IRC 83W E26/50x39/BRC 120V FL 25D

