



- NOTES:
1. MAXIMUM CONTINUOUS LINE TO GROUND OPERATING VOLTAGE, 335 KV RMS.
 2. DUTY CYCLE VOLTAGE RATING 420 KV
 3. NET WEIGHT 580lbs (263.6kg)
 4. DIMENSIONS SUBJECT TO ± 3% TOLERANCE
 5. LEAKAGE DISTANCE - 486.6 (12359)
 6. DIMENSIONS ARE INCHES (MM)
 7. CLAMP TYPE GROUND TERMINALS SUITABLE FOR COPPER OR ALUMINUM CONDUCTORS .25(7) - .81(21)

.5 μs SEC 10KA IR KV	2 KA SWITCHING	MAX IR USING 8 X 20 μs CURRENT WAVE KV	30 KA	5 KA	10 KA	20 KA	40 KA
	SURGE IR KV	1.5 KA	865	902	963	1043	1161
1063	832	825					

ANSI STATION CLASS ARRESTER

OHM-BRASS TOLERANCE CHART

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PART OF THIS DRAWING OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. UNPUBLISHED COPYRIGHT LAWS.

HUBBELL POWER SYSTEMS

ARRESTER SVN 335 KV MCOV

REV 0

DATE 06/29/07

REV DATE 06/29/07